


STARR ROAD RESIDENTIAL PUD STARR ROAD CORTLANDVILLE, NEW YORK

PREPARED BY:

TIMOTHY C. BUHL P.E.
35 FIRE LANE 24
AUBURN, NY 13021





• LOCATION MAP •
N.T.S.

DATE: SEPTEMBER 10, 2018

DRAWING INDEX

T-1	TITLE SHEET
PUD-1	PROPOSED SITE PLAN
ST-1	GRADING PLAN
ST-2	SITE DETAILS
ST-3	SITE DETAILS
ST-4	PLANTING PLAN
ST-5	PRELIM ROAD SECTION
ST-6	ESC PLAN
ST-7	ESC DETAILS
ST-8	INFILTRATION BASIN PLAN DETAILS
ST-9	INFILTRATION BASIN SECTION
ST-10	BIORETENTION AREA DETAILS 2
ST-11	TYPICAL RAIN GARDEN DETAILS
ST-12	HYDROLOGIC AND HYDRAULIC WORKSHEET EXISTING COND.
ST-13	HYDROLOGIC AND HYDRAULIC WORKSHEET PROPOSED COND. -1
ST-14	HYDROLOGIC AND HYDRAULIC WORKSHEET PROPOSED COND. -2
ST-15	HYDROLOGIC AND HYDRAULIC WORKSHEET PROPOSED COND. -3
ST-16	UTILITY SITE PLAN
ST-17	SANITARY PROFILE
ST-18	WATER PROFILE
ST-19	SANITARY AND WATER DETAILS
ST-20	PHOTOMETRIC SITE PLAN
ST-21	SIGN LOCATION PLAN & DETAILS



LEGEND :

- SNOW STORAGE =
- PEDESTRIAN PATH =
- BUILDING LIGHT =
- STREET LIGHT =
- WATER VALVE =
- PLAY/PICNIC AREA (SEE ST-3 FOR DESCRIPTIONS) =
- DUPLEX =
- MULTI FAMILY =
- RAIN GARDEN/BIO-SWALE =

NOTES: 3 NEW ORNAMENTAL TREES PER D/U TO BE SCATTERED THROUGHOUT THE SITE; SIZE & CALIPER AS REQUIRED BY TOWN ORDINANCE
EXISTING TREES ALONG PROPERTY BOUNDARIES TO REMAIN AS A BUFFER


PROJECT DENSITY:
 3 - 8 MULTI FAMILY HOMES - 24 DWELLINGS
 1 - 6 MULTI FAMILY HOMES - 6 DWELLINGS
 10 - DUPLEX HOMES - 20 DWELLINGS
 50 TOTAL DWELLINGS/11.6 ACRES = 4.3 DU/AC
 BASE DENSITY 9,600 SF/DU (R-2) = 4.5 DU/AC
 AT 50 UNITS NO INCENTIVE INCREASE REQUIRED

PARKING SUMMARY:
 30 MULTI FAMILY UNITS - 60 SPACES
 10 DUPLEX UNITS - 20 SPACES (+ GARAGES)
 COMMUNITY BUILDING/FITNESS CENTER - 20 SPACES
 TOTAL PARKING SPACES PROVIDED - 100 SPACES

EXISTING CONDITIONS:
 OPEN FIELD, BRUSH & WOODS.
 TOTAL = 505,296 S.F.(11.6 AC+/-)
PROPOSED CONDITIONS:
 BUILDINGS = 50,128 S.F. (1.2 AC)
 PARKING = 79,562 S.F. (1.8 AC)
 DRIVE/WALK = 30,638 S.F. (.7 AC)
 STORMWATER = 52,272 S.F.(1.2 AC)
 BRUSH/WOODS = 69,696 SF(1.6 AC)


REVISIONS	
No.	Description

PROPOSED SITE PLAN
 STARR RD. RESIDENTIAL PUD
 STARR ROAD
 CORTLANDVILLE (T) N.Y.
 LEONIDAS GRP. OF VIRGIL, LLC
 5 SOUTH ST.-PO BOX 1107
 DRYDEN, N.Y. 13053



TIMOTHY C. BUHL, P.E.
 35 FIRE LANE 24, AUBURN, N.Y. 13021 607.423.1919

DATE: 9-10-2018
 SCALE: 1" = 50'
 DRAWN: MB/JLB
 JOB: 1432
 SHEET: PUD-1



No.	Date	SYMBOL	DESCRIPTION

GRADING PLAN



STARR RD. RESIDENTIAL PUD
 LEONIDAS GRP. OF VIRGIL, LLC
 5 SOUTH ST., PO BOX 1107
 CORTLANDVILLE (T) N. Y.



TIMOTHY C. BUHL, P.E.


35 FIRELANE 24, AUBURN, N.Y. 13021 607-423-1919

DATE: 9-10-2018
 SCALE: 1" = 50'
 DRAWN: MB/JLB
 JOB: 17-14
 SHEET: ST-1




- NOTES:**
1. PROVIDE 1/4" WIDE CONTROL JOINTS TOOLED OR SAWN, 1-1/2" DEPTH AT SPACING NO GREATER THAN THE SIDEWALK WIDTH. SPACING SHALL BE ADJUSTED FOR EACH SEGMENT OF SIDEWALK SO THAT THE SEGMENT LENGTHS WILL REMAIN CONSISTENT THROUGHOUT EACH LENGTH OF SIDEWALK.
 2. PROVIDE 1/2" WIDE EXPANSION JOINTS, FILLER AS SPECIFIED-RECESS 1/4". FILL RECESS WITH SEALANT. EXPANSION JOINT SPACING NOT TO EXCEED 25'-0" IN ANY DIRECTION AND AT CONTACT WITH WALLS, STEPS, DOORS, OR OTHER VERTICAL SURFACES.
 3. PROVIDE BROOM FINISH PERPENDICULAR TO DIRECTION OF TRAFFIC.

SECTION - CONCRETE SIDEWALK




- NOTES:**
1. ALL DEPTHS OF MATERIAL ARE AFTER COMPACTION.

SECTION - ASPHALT PAVEMENT HEAVY DUTY




CURB TRANSITION




- NOTES:**
1. PROVIDE 1/2" EXPANSION JOINTS AT 30'-0" ON CENTER (MAX). USE ASPHALT IMPREGNATED PREMOLD FILLER.
 2. CONTROL JOINTS AT 10'-0" ON CENTER (MAX) SPACE JOINTS EVENLY BETWEEN EXPANSION JOINTS.
 3. USE WHERE CONCRETE WALK MEETS CONCRETE CURB.

INTEGRAL CURB AND SIDEWALK




- NOTES:**
1. PROVIDE 1/2" EXPANSION JOINTS AT 30'-0" ON CENTER (MAX). USE ASPHALT IMPREGNATED PREMOLD FILLER.
 2. CONTROL JOINTS AT 10'-0" ON CENTER (MAX) SPACE JOINTS EVENLY BETWEEN EXPANSION JOINTS.

INTEGRAL FLUSH CURB AND SIDEWALK




TYPICAL LAYOUT - MACHINE INSTALLED CLUSTER (ECO-DUBLIN PATTERN)



PERVIOUS UNIT PAVER

PRODUCT INFORMATION:
 BELGARD "ECO DUBLIN" PERMEABLE CONCRETE PAVER. FOSSIL BEIGE COLOR. SMOOTH FINISH. CONTACT INFO: 877-235-4273 OR WWW.BELGARD.COM




- NOTES:**
1. ALL PAVEMENT MARKINGS SHALL BE PLACED IN ACCORDANCE WITH SUBCHAPTER "E" OF THE NEW YORK STATE MANUAL OF UNIFORM TRAFFIC CONTROL DEVICES (M.U.T.C.D.). LINE WIDTHS AND SPACING SHALL BE THE SAME AS INDICATED ON DRAWINGS.
 2. AFTER THE CONTRACTOR HAS ESTABLISHED MARKING LINE POINTS FOR THE MARKINGS, AS PER SECTION 687.3.04 OF THE N.Y.S.S STANDARD SPECIFICATIONS, CONSTRUCTION AND MATERIALS, JANUARY 2, 1985, BY PAINT OR OTHER APPROVED MEANS, THE E.I.C. SHALL REVIEW AND APPROVE OR REVISE THESE LOCATIONS TO MEET FIELD CONDITIONS. NECESSARY LOCATION ADJUSTMENTS WILL BE MADE PRIOR TO PLACING PAVEMENT MARKINGS


ACCESSIBLE PARKING STALL PLAN

SIGNAGE SCHEDULE			
TYPE	SIGN	QUANTITY	DESCRIPTION
1	TRAFFIC CONTROL	87.6	12" x 18" RECTANGULAR SIGN ON WHITE
2	NO PARKING	87.8a	12" x 18" RECTANGULAR SIGN ON WHITE
3	NO PARKING	87.8	12" x 18" RECTANGULAR SIGN ON WHITE
4	STOP	87.9	36" x 36" OCTAGONAL WHITE ON RED

- NOTES:**
1. ALL TRAFFIC CONTROL SIGNAGE SHALL CONFORM TO MANUAL OF UNIFORM TRAFFIC CONTROL DEVICES (M.U.T.C.D.) AND NYS DOT STANDARDS. SEE DRAWING C-100 FOR SIGNAGE LOCATION AND DETAIL & C-105 FOR INSTALLATION. GRAPHICS AND LETTERING FOR LETTERS AND SYMBOLS.
 2. ALL SIGNS TO BE INSTALLED ON 600 MIN ALUMINUM SIGN WITH PREPERFORATED HOLES AND BAKED ENAMEL FINISH. SIGNSHIELD GRAPHICS AND LETTERING FOR LETTERS AND SYMBOLS.
 3. ALL SIGNS TO BE INSTALLED ON 2" SQUARE STEEL POST WITH 4" HOLES AT 2' ON CENTER.




DYNAMIC ACCESSIBLE SYMBOL



- NOTE:**
1. BASIS OF DESIGN SHALL BE: ARMOR-TILE CAST IN PLACE DETECTABLE WARNING TILE. COLOR: COLONIAL RED. BY: ENGINEERED PLASTICS, INC. PHONE: 800-682-2525. WWW.ARMOR-TILE.COM. OR APPROVED EQUAL.

DETECTABLE WARNING STRIP



- NOTE:**
1. 4" DEPTH, 4000 PSI CONCRETE PAVEMENT WITH 6" DEPTH AGGREGATE BASE COURSE. PROVIDE 6x6, W2.9 x W2.9 WWM REINFORCING. BROOM FINISH PERPENDICULAR TO DIRECTION OF TRAFFIC.


ACCESSIBLE CURB RAMP

REVISIONS

No.	Date	SYMBOL	Description

SITE DETAILS



LEONIDAS GRP. OF VIRGIL, LLC
 5 SOUTH ST., PO BOX 1107
 DRYDEN, N.Y. 13053




TIMOTHY C. BUHL, P.E.

35 FIRE LANE 24, AUBURN, N.Y. 13021 607 423-1919


DATE: 9-10-18
 SCALE: NONE
 DRAWN: MB/JLB
 JOB: 17-14
 SHEET: ST-2



MULCH PLANTING BED



PLAN VIEW - TRIANGULAR SPACING: NOT TO SCALE





SHRUB PLANTING

PLANTING SCHEDULE							
KEY	BOTANICAL NAME	COMMON NAME	ROOT	SIZE	SPACING	NOTES	QUANTITY
DECIDUOUS TREES							
AC	AMELANCHIER CANADENSIS 'AUTUMN BRILLIANCE'	AUTUMN BRILLIANCE SERVICEBERRY	B & B	8-10' HT	10'-0" OC	MULTI-STEM	16
BN	BETULA NIGRA 'HERITAGE'	HERITAGE RIVER BIRCH	B & B	8-10' HT	AS SHOWN	MULTI-STEM	11
CC	CRATAEGUS CRUSGALLI INERMIS 'CRUSADER'	CRUSADER THORNLESS COCKSPUR HAWTHORN	B & B	2 1/2-3' CAL	10'-0" OC	THORNLESS VARIETY	25
EVERGREEN TREES							
PA	PICEA ABIES	NORWAY SPRUCE	B & B	7-8' HT	15'-0" OC	-	46
PN	PINUS NIGRA	AUSTRIAN PINE	B & B	7-8' HT	15'-0" OC	-	65
DECIDUOUS SHRUBS							
CA	CLETHIA ALNIFOLIA 'COMPACTA'	COMPACT SUMMERSWEET CLETHRA	#2 CONT	-	3'-0" OC	DWARF VARIETY	43
PF	POTENTILLA FRUITICOSA 'PRINCESS'	PRINCESS POTENTILLA	#2 CONT	-	3'-0" OC	PINK FLOWER VARIETY	62
EVERGREEN SHRUBS							
IG	ILEX GLABRA COMPACTA 'SHAMROCK'	SHAMROCK COMPACT INKBERRY	B & B	24-30" HT	4'-0" OC	COMPACT FORM	60
JH	JUNIPER HORIZONTALIS 'BLUE CHIP'	BLUE CHIP JUNIPER	#2 CONT	-	3'-0" OC	-	141
TO	THUJA OCCIDENTALIS 'NIGRA'	DARK AMERICAN ARBORVITAE	B & B	6-7' HT	6'-0" OC	-	12
PERENNIALS / ORNAMENTAL GRASSES / GROUND COVER							
HP	HEMERCALLIS 'PARDON ME'	PARDON ME DAYLILLY	#1 CONT	-	2'-0" OC	RED FLOWER	107
HS	HEMERCALLIS 'STELLA D'ORO'	STELLA D'ORO DAYLILLY	#1 CONT	-	2'-0" OC	YELLOW FLOWER	111
RA	RHUS AROMATIC 'GRO-LOW'	GROW-LOW SUMAC	#2 CONT	18-24" HT	4'-0" OC	-	48


NOTES:
1. AT PLAYGROUNDS PROVIDE 12 EACH RA TYPE PLANTS.

SYMBOLS
B & B - BALLED & BURLAPPED
CAL - CALIPER
CONT - CONTAINER




- NOTES:**
- REFERENCE PLAN FOR ADJACENT PLANTING CONDITIONS.
 - DO NOT CUT CENTRAL LEADER.
 - SET TREE WITH 3" MAX. ROOT BALL ABOVE FINISH GRADE.
 - PROVIDE "TREE GATOR" 20 GALLON BAG DRIP IRRIGATION SYSTEM BY MEGADROW, WWW.MEGADROW.COM, OR EQUAL, ON ALL NEW TREE PLANTINGS.

TREE PLANTING




- NOTES:**
- REFER TO MANUFACTURERS INSTALLATION INSTRUCTIONS FOR DEPTH AND SIZE OF FOOTING.

TYPICAL PLAYGROUND STRUCTURE FOOTING




- NOTES:**
- REFER TO MANUFACTURERS INSTALLATION INSTRUCTIONS FOR DEPTH AND SIZE OF FOOTING.

WEAR MAT PLACEMENT



PLAYGROUND SURFACING



LIGHT POLE - PARKING LOTS

PLAYGROUND EQUIP. - SELECTION TABLE	
MODEL NAME	MODEL NUMBER
COZY COCOON	ZZX0483
CUSTOM MINNOW NAUTICAL THEMED SHIP	350-1516
TRANSFER STATION WITH STEP	-
T POST SWING W/2 TOT SEATS	ZZX0290 ZZX0325
WAVERIDER SEESAW	ZZX0650
6 FT LONG PERMANENT ANGLE LEG BENCH	ZZX9010
BARRIER FREE BI-LEVEL STAINLESS STEEL DRINKING FOUNTAIN	GRM45
ROCKBLOCKS STALAGMITE CLIMBER	ZZUN8246
LONG FREE-STANDING TIMBER TRAIL BRIDGE	ZZUN8479
CUSTOM TREE HOUSE THEMED PLAY STRUCTURE	-
6 FT ROPE BRIDGE	ZZCH6398
THE SKY ARCH	ZZCH8456
CRITTER CROSSING	ZZCH6857
DROP ZONE (48" DECK)	ZZUN7026
8 FT TOWER CLIMBER	ZZCH6839
WILDWOOD CLIMBER (48" DECK)	ZZCH6839
360 DEGREE SLITHER SPIRAL SLIDE	-
VORTEX	ZZCH6810
SINGLE POST SWING	ZZX0295

- PLAYGROUND NOTES:**
- BASIS OF DESIGN FOR PLAY COMPONENTS: LANDSCAPE STRUCTURES, INC., 601 7TH STREET SOUTH, DELANO, MN 55328, PH: 763-972-3391, www.playlsl.com, OR APPROVED EQUAL.
 - BASIS OF DESIGN FOR PLAY AREA SAFETY SURFACING: ENGINEERED WOOD FIBER BY ZEAGER BROTHERS, INC., 4000 EAST HARRISBURG PIKE, MIDDLETON, PA 17057, PH: 1-800-346-8524, www.zeager.com, OR APPROVED EQUAL.
 - INSTALL PLAY COMPONENTS IN ACCORDANCE TO MANUFACTURER'S WRITTEN INSTRUCTIONS AND SPECIFICATIONS.
 - PLAYGROUND EQUIPMENT TO BE INSTALLED IN GROUPS PER AGE-APPROPRIATION AT EACH LOCATION - SEE BELOW.

- PLAYGROUND/PICNIC PLAN LEGEND:**
- PICNIC AREA - TWO PICNIC TABLES W/UMBRELLAS, 2 ADERONACK CHAIRS, FIXED OUTDOOR GRILL, NO PLAY FEATURES.
 - PLAY A - PREDOMINATELY FOR 6-24 MONTHS; DUAL TODDLER SWING SET, ONE CLIMBING AND ONE CRAWLING FEATURE, ONE MINI-SLIDE, ONE DIGI-RIDER PLUS ONE PICNIC TABLE AND UMBRELLA.
 - PLAY B - PREDOMINATELY FOR 2-5 YEARS; DUAL CHILD SWING SET, MEDIUM SLIDE, ONE NETS COURSE, ONE CLIMBING FEATURE, PLUS ONE PICNIC TABLE AND UMBRELLA.
 - PLAY C - PREDOMINATELY FOR 6-12 YEARS; DUAL STANDARD SWING SET, ONE TUBE SLIDE WITH CLIMBING FEATURE, MEDIUM ROPES/NET COURSE, PLUS ONE PICNIC TABLE AND UMBRELLA.
 - TABLE AT LEFT IS REPRESENTATIVE OF THE THE NUMBER, STYLE AND QUALITY OF THE FEATURES PLANNED; THE DEVELOPER RESERVES THE RIGHT TO MAKE SELECTIONS AND SUBSTITUTIONS AS NECESSARY.

REVISIONS

No.	Date	SYMBOL	Description

SITE DETAILS


LEONIDAS GRP. OF VIRGIL, LLC
5 SOUTH ST., PO BOX 1107
CORTLANDVILLE (T) N.Y.




TIMOTHY C. BUHL, P.E.

35 FIRELANE 24, AUBURN, N.Y. 13021 607-423-1919


DATE: 9-10-2018
SCALE: NONE
DRAWN: MB/JLB
JOB: 17-14
SHEET: ST-3




TYPICAL 6 and 8 MULTI UNIT PLANTING PLAN




COMMUNITY CENTER PLANTING PLAN




TYPICAL SINGLE/DUPLEX UNIT PLANTING PLAN



LANDSCAPE BUFFER



LANDSCAPE BUFFER




No.	Date	SYMBOL	REVISIONS Description

PLANTING PLANS
 STARR RD. RESIDENTIAL PUD LEONIDAS GRP. OF VIRGIL, LLC
 STARR ROAD 5 SOUTH ST., PO BOX 1107
 CORTLANDVILLE (T) N. Y. DRYDEN, N. Y. 13053





TIMOTHY C. BUHL, P.E.
 35 FIRELANE 24, AUBURN, N.Y. 13021 607-423-1919

DATE: 9-10-2018
 SCALE: NONE
 DRAWN: MB/JLB
 JOB: 17-14
 SHEET: ST-4



NOTE: ROADWAY, WATER SUPPLY PIPING, & SEWER COLLECTION PIPING ARE ALL TO BE PRIVATELY OWNED, OPERATED, AND MAINTAINED.



REVISIONS	
No.	Description

PRELIM ROAD SECTION


LEONIDAS GRP. OF VIRGL, LLC
5 SOUTH ST., PO BOX 1107
DRYDEN, N.Y. 13053

STARR RD. RESIDENTIAL PUD
STARR ROAD
CORTLANDVILLE (D) N.Y.

TIMOTHY C. BUHL, P.E.

35 FIRE LANE 24, AUBURN, N.Y. 13021 607.423.1919

DATE: 9-10-2018
SCALE: 1" = 50'
DRAWN: MB/JLB
JOB: 17-14
SHEET: ST-5



No.	Date	SYMBOL	REVISIONS Description

ESC PLAN
 STARR RD. RESIDENTIAL PUD
 LEONIDAS GRP. OF VIRGIL, LLC
 STARR ROAD
 CORTLANDVILLE (T) N.Y.
 5 SOUTH ST.-PO BOX 1107
 DRYDEN, N.Y. 13053



TIMOTHY C. BUHL, P.E.
 35 FIRE LANE 24, AUBURN, N.Y. 13021 607-423-1919

DATE: 9-10-2018
 SCALE: 1" = 50'
 DRAWN: MB/JLB
 JOB: 17-14
 SHEET: ST-6

GENERAL NOTES

NYS STANDARDS AND SPECIFICATIONS FOR EROSION AND SEDIMENT CONTROL, NOVEMBER 2016

- PHYSICALLY MARK LIMITS OF LAND DISTURBANCE ON THE SITE WITH TAPE, SIGNS, OR ORANGE CONSTRUCTION FENCE, SO THAT WORKERS CAN SEE THE AREAS TO BE PROTECTED.
- DIVERT OFF-SITE RUNOFF FROM HIGHLY ERODIBLE SOILS AND STEEP SLOPES TO STABLE AREAS.
- CLEAR ONLY WHAT IS REQUIRED FOR IMMEDIATE CONSTRUCTION ACTIVITY. LARGE PROJECTS SHOULD BE CLEARED AND GRADED AS CONSTRUCTION PROGRESSES. AREAS EXCEEDING TWO ACRES IN SIZE SHOULD NOT BE DISTURBED WITHOUT A SEQUENCING PLAN THAT REQUIRES PRACTICES TO BE INSTALLED AND THE SOIL STABILIZED. AS DISTURBANCE BEYOND THE TWO ACRES CONTINUES, MASS CLEARINGS AND GRADING OF ENTIRE SITE SHOULD BE AVOIDED.
- RESTABILIZE DISTURBED AREAS AS SOON AS POSSIBLE AFTER CONSTRUCTION IS COMPLETED. ON SITES GREATER THAN TWO ACRES IN SIZE, WAITING UNTIL ALL DISTURBED AREAS ARE READY FOR SEEDING IS UNACCEPTABLE. FOURTEEN DAYS SHALL BE THE MAXIMUM EXPOSURE PERIOD. MAINTENANCE MUST BE PERFORMED AS NECESSARY TO ENSURE CONTINUED STABILIZATION. EXCEPT AS NOTED BELOW, ALL SITES SHALL BE SEEDED AND STABILIZED WITH EROSION CONTROL MATERIALS, SUCH AS STRAW MULCH, JUTE MESH, OR EXCLESIOR, INCLUDING AREAS WHERE CONSTRUCTION HAS BEEN SUSPENDED OR SECTIONS COMPLETED:
 - FOR ACTIVE CONSTRUCTION AREAS SUCH AS BORROW OR STOCKPILE AREAS, ROADWAY IMPROVEMENTS AND AREAS WITHIN 50 FT. OF A BUILDING UNDER CONSTRUCTION, A PERIMETER SEDIMENT CONTROL SYSTEM CONSISTING, FOR EXAMPLE, OF SILT FENCING OR HAY BALES, SHALL BE INSTALLED AND MAINTAINED TO CONTAIN SOIL. EXPOSED DISTURBED AREAS ADJACENT TO A CONVEYANCE THAT PROVIDES RAPID OFF-SITE DISCHARGE OF SEDIMENT, SUCH AS A CUT SLOPE AT AN ENTRANCE, SHALL BE COVERED WITH PLASTIC OR, GEOTEXTILE FABRIC TO PREVENT SOIL LOSS UNTIL IT CAN BE STABILIZED. STABILIZED CONSTRUCTION ENTRANCES WILL BE MAINTAINED TO CONTROL VEHICLE TRACKING MATERIAL OFF-SITE.
 - ON THE CUT SIDE OF ROADS, DITCHES SHALL BE STABILIZED IMMEDIATELY WITH ROCK RIP-RAP OR OTHER NON-ERODIBLE LINERS (EG. ROLLED EROSION PRODUCTS), OR WHERE APPROPRIATE, VEGETATIVE MEASURES SUCH AS SOD.
 - PERMANENT SEEDING SHOULD OPTIMALLY BE UNDERTAKEN IN THE SPRING FROM MARCH THROUGH MAY, AND IN LATE SUMMER AND EARLY FALL FROM SEPTEMBER TO OCTOBER 15. DURING THE PEAK SUMMER MONTHS AND IN THE FALL AFTER OCTOBER 15, WHEN SEEDING IS FOUND TO BE IMPRACTICABLE, AN APPROPRIATE TEMPORARY MULCH SHALL BE APPLIED. PERMANENT SEEDING MAY BE UNDERTAKEN DURING THE SUMMER IF PLANS PROVIDE FOR ADEQUATE WATERING. TEMPORARY SEEDING WITH RYE CAN BE UTILIZED THROUGH NOVEMBER.
 - ALL SLOPES STEEPER THAN 3:1 (H:V), OR 33.3%, AS WELL AS PERIMETER DIKES, SEDIMENT BASINS AND TRAPS, AND EMBANKMENTS SHALL, UPON COMPLETION, BE IMMEDIATELY STABILIZED WITH SOD, SEED AND ANCHORED STRAW MULCH, OR OTHER APPROVED STABILIZATION MEASURES. AREAS OUTSIDE OF THE PERIMETER SEDIMENT CONTROL SYSTEM SHALL NOT BE DISTURBED. MAINTENANCE SHALL BE PERFORMED AS NECESSARY TO ENSURE CONTINUED STABILIZATION.
 - TEMPORARY SEDIMENT TRAPPING DEVICES SHALL NOT BE REMOVED UNTIL PERMANENT STABILIZATION IS ESTABLISHED IN ALL CONTRIBUTORY DRAINAGE AREAS. SIMILARLY, STABILIZATION SHALL BE ESTABLISHED PRIOR TO CONVERTING SEDIMENT TRAPS/BASINS INTO PERMANENT (POST-CONSTRUCTION) STORMWATER MANAGEMENT PRACTICES.

IF TEMPORARY WORK ROADS OR HAIL ROADS CROSS STREAM CHANNELS, ADEQUATE WATERWAY OPENINGS SHALL BE CONSTRUCTED USING SPANS, CULVERTS, WASHED ROCK BACKFILL, OR OTHER ACCEPTABLE, CLEAN METHODS THAT WILL ENSURE THAT ROAD CONSTRUCTION AND THEIR USE DO NOT RESULT IN TURBIDITY AND SEDIMENT DOWNSTREAM. ALL CROSSING ACTIVITIES AND APPURTENANCES ON STREAMS REGULATED BY ARTICLE 15 OF THE ENVIRONMENTAL CONSERVATION LAW SHALL BE IN COMPLIANCE WITH A PERMIT ISSUED PURSUANT TO ARTICLE 15 OF THE ECL.

MAKE SURE THAT ALL CONTRACTORS AND SUB-CONTRACTORS UNDERSTAND THE ESC PLAN AND SIGN THE CERTIFICATION STATEMENT REQUIRED BY NYSDEC GP.


DESIGNATE RESPONSIBILITY FOR THE ESC PLAN TO ONE INDIVIDUAL. THIS PERSON SHALL BE NAMED IN THE NOTICE OF INTENT.

AN ESC PLAN INSPECTION PROGRAM MEETING THE REQUIREMENTS OF THE NYSDEC GP, IS NECESSARY TO DETERMINE WHEN ESC MEASURES NEED MAINTENANCE OR REPAIR. PAY PARTICULAR ATTENTION TO INSPECTIONS REQUIRED AFTER RAINFALL. THE INSPECTION PROGRAM SHALL ALSO STATE THE COMPLETION OF IDENTIFIED REPAIR AND MAINTENANCE ITEMS.

IF CONSTRUCTION ACTIVITIES CONTINUE DURING WINTER, ACCESS POINTS SHOULD BE ENLARGED AND STABILIZED TO PROVIDE FOR SNOW STOCKPILING. IN ADDITION SNOW MANAGEMENT PLAN SHOULD BE PREPARED WITH ADEQUATE STORAGE AND CONTROL OF MELTWATER. A MINIMUM 25 FOOT BUFFER SHALL BE MAINTAINED FROM PERIMETER CONTROLS SUCH AS SILT FENCING. KEEP DRAINAGE STRUCTURES OPEN AND FREE OF SNOW AND ICE DAMS. INSPECTION AND MAINTENANCE ARE NECESSARY TO ENSURE THE FUNCTION OF THESE PRACTICES DURING RUNOFF EVENTS.

LAND GRADING SPECIFICATIONS

- ALL FILLS SHALL BE COMPACTED AS REQUIRED TO REDUCE EROSION, SLIPPAGE, SETTLEMENT, SUBSIDENCE OR OTHER RELATED PROBLEMS. FILL INTENDED TO SUPPORT BUILDINGS, STRUCTURES AND CONTAINERS, ETC. SHALL BE COMPACTED IN ACCORDANCE WITH LOCAL REQUIREMENTS OR CODES.
- ALL FILL TO BE PLACED AND COMPACTED IN LAYERS NOT TO EXCEED 9 INCHES IN THICKNESS.
- FILL MATERIAL SHALL BE FREE OF FROZEN PARTICLES, BRUSH, ROOTS, SOD, OR OTHER FOREIGN OR OTHER OBJECTIONABLE MATERIALS THAT WOULD INTERFERE WITH OR PREVENT CONSTRUCTION OF SATISFACTORY FILLS.
- SEEPS OR SPRINGS ENCOUNTERED DURING CONSTRUCTION SHALL BE HANDLED IN ACCORDANCE WITH THE STANDARD AND SPECIFICATION FOR SUBSURFACE DRAIN OR OTHER APPROVED METHOD.
- STOCKPILES, BORROW AREAS AND SPOIL AREAS SHALL BE SHOWN ON THE PLANS AND SHALL BE SUBJECT TO THE PROVISIONS OF THIS STANDARD AND SPECIFICATION.




CONSTRUCTION SPECIFICATIONS

- STONE SIZE - USE 2" STONE OR RECLAIMED OR RECYCLED CONCRETE EQUIVALENT.
- LENGTH - NOT LESS THAN 50 FEET (EXCEPT ON A SINGLE RESIDENCE LOT WHERE A 30 FOOT MIN. LENGTH WOULD APPLY).
- THICKNESS - NOT LESS THAN SIX (6) INCHES.
- WIDTH - TWELVE (12) FOOT MIN. BUT NOT LESS THAN THE FULL WIDTH AT POINTS WHERE INGRESS OR EGRESS OCCURS. TWENTY-FOUR (24) FOOT IF SINGLE ENTRANCE TO SITE.
- FILTER CLOTH - WILL BE PLACED OVER THE ENTIRE AREA PRIOR TO PLACING OF STONE.
- SURFACE WATER - ALL SURFACE WATER FLOWING OR DIVERTED TOWARD CONSTRUCTION ENTRANCES SHALL BE PIPED ACROSS THE ENTRANCE. IF PIPING IS IMPRACTICAL, A MOUNTABLE BERM WITH 5:1 SLOPES WILL BE PERMITTED.
- MAINTENANCE - THE ENTRANCE SHALL BE MAINTAINED IN A CONDITION WHICH WILL PREVENT TRACKING OR FLOWING OF SEDIMENT ONTO PUBLIC RIGHTS-OF-WAY. ALL SEDIMENT SPILLED, DROPPED, WASHED OR TRACED ONTO PUBLIC RIGHTS-OF-WAY MUST BE REMOVED IMMEDIATELY.
- WHEN WASHING IS REQUIRED, IT SHALL BE DONE ON AN AREA STABILIZED WITH STONE AND WHICH DRAINS INTO AN APPROVED SEDIMENT TRAPPING DEVICE.
- PERIODIC INSPECTION AND NEEDED MAINTENANCE SHALL BE PROVIDED AFTER EACH RAIN.
- TEMPORARY CONSTRUCTION ENTRANCES, EXITS AND TEMPORARY ACCESS SHALL BE SUBJECT TO THE APPROVAL OF THE APPROPRIATE AUTHORITIES.

TOP SOILING SPECIFICATIONS


- PRESERVE EXISTING TOPSOIL IN PLACE WHERE POSSIBLE, THEREBY REDUCING THE NEED FOR ADDED TOPSOIL.
- AS NEEDED, INSTALL EROSION CONTROL PRACTICES SUCH AS DIVERSIONS, CHANNELS, SEDIMENT TRAPS, AND STABILIZING MEASURES, OR MAINTAIN IF ALREADY INSTALLED.
- COMPLETE ROUGH GRADING AND FINAL GRADE, ALLOWING FOR DEPTH OF TOPSOIL TO BE ADDED.
- SCARIFY ALL COMPACT, SLOWLY PERMEABLE, MEDIUM AND FINE TEXTURED SUBSOIL AREAS. SCARIFY AT APPROXIMATELY RIGHT ANGLES TO THE SLOPE DIRECTION IN SOIL AREAS THAT ARE STEEPER THAN 5%. AREAS THAT HAVE BEEN OVERLY COMPACTED SHALL BE DECOMPACTED TO A MINIMUM DEPTH OF 12-INCHES WITH A DEEP RIPPER OR CHISEL PLOW PRIOR TO TOPSOILING.
- REMOVE REFUSE, WOODY PLANT PARTS, STONES OVER 3-INCHES IN DIAMETER, AND OTHER LITTER.
- TOPSOIL SHALL HAVE AT LEAST 6% BY WEIGHT OF FINE TEXTURED STABLE ORGANIC MATERIAL, AND NO GREATER THAN 20% MUCK SOIL SHALL NOT BE CONSIDERED TOPSOIL.
- TOPSOIL SHALL HAVE NOT LESS THAN 20% FINE TEXTURED MATERIAL (PASSING THE NO. 200 SIEVE) AND NOT MORE THAN 15% CLAY.
- TOPSOIL TREATED WITH SOIL STERILANTS OR HERBICIDES SHALL BE SO IDENTIFIED TO THE PURCHASER.
- TOPSOIL SHALL BE RELATIVELY FREE OF STONES OVER 1 1/2-INCHES IN DIAMETER, TRASH, NOXIOUS WEEDS SUCH AS NUT SEDGE AND QUACKGRASS, AND WILL HAVE LESS THAN 10% GRAVEL.
- TOPSOIL CONTAINING SOLUBLE SALTS GREATER THAN 500 PARTS PER MILLION SHALL NOT BE USED.
- TOPSOIL SHALL BE DISTRIBUTED TO A UNIFORM DEPTH OVER THE AREA. IT SHALL NOT BE PLACED WHEN IT IS PARTIALLY FROZEN, MUDDY, OR ON FROZEN SLOPES OR OVER ICE, SNOW, OR STANDING WATER PUDDLES.
- TOPSOIL PLACED AND GRADED ON SLOPES STEEPER THAN 5% SHALL BE PROMPTLY FERTILIZED, SEEDED, MULCHED, AND STABILIZED BY "TRACKING" WITH SUITABLE EQUIPMENT.



CONSTRUCTION SPECIFICATIONS


GRASSED/VEGETATED SWALE

- DRAINAGE AREA SHALL BE LESS THAN 5 ACRES.
- HEIGHT SHALL BE NO LESS THAN 18-INCHES FROM BOTTOM OF SWALE TO TOP OF DIKE EVENLY DIVIDED BETWEEN DIKE HEIGHT AND SWALE DEPTH.
- BOTTOM WIDTH OF DIKE SHALL BE NO LESS THAN 2-FEET.
- WIDTH OF SWALE SHALL BE NO LESS THAN 2-FEET.
- SWALE SHALL HAVE POSITIVE DRAINAGE TO AN ADEQUATELY STABILIZED OUTLET TO AN UNDISTURBED AREA. MAXIMUM ALLOWABLE GRADE NOT TO EXCEED 8%.
- THE DISTURBED AREA OF THE DIKE AND SWALE SHALL BE STABILIZED WITHIN 7 DAYS OF INSTALLATION, IN ACCORDANCE WITH THE STANDARD SPECIFICATIONS FOR TEMPORARY SWALES. USE TRM'S WHERE REQUIRED TO ESTABLISH PERMANENT VEGETATION. INSTALL PER MFG'S RECOMMENDATIONS.
- DIVERTED RUNOFF FROM A DISTURBED OR EXPOSED UPLAND AREA SHALL BE CONVEYED TO A SEDIMENT TRAPPING DEVICE SUCH AS A TRAP, BASIN, OR TO AN AREA PROTECTED BY ANY OF THESE PRACTICES.
- PERIODIC INSPECTION AND REQUIRED MAINTENANCE MUST BE PROVIDED AFTER EACH RAIN EVENT.




CONSTRUCTION SPECIFICATIONS

- WOVEN WIRE FENCE TO BE FASTENED SECURELY TO FENCE POSTS WITH WIRE TIES OR STAPLES. POSTS SHALL BE STEEL EITHER "T" OR "U" TYPE OR HARDWOOD.
- FILTER CLOTH TO BE TO BE FASTENED SECURELY TO WOVEN WIRE FENCE WITH TIES SPACED EVERY 24" AT TOP AND MID SECTION. FENCE SHALL BE WOVEN WIRE, 12 1/2 GAUGE, 6" MAXIMUM MESH OPENING.
- WHEN TWO SECTIONS OF FILTER CLOTH ADJOIN EACH OTHER THEY SHALL BE OVERLAPPED BY SIX INCHES AND FOLDED. FILTER CLOTH SHALL BE EITHER FILTER X, MIRAFI 100X, STABILINKA T1-40N, OR APPROVED EQUIVALENT.
- PREFABRICATED UNITS SHALL BE GEOFAB, ENVIROFENCE, OR APPROVED EQUIVALENT.
- MAINTENANCE SHALL BE PERFORMED AS NEEDED AND MATERIAL REMOVED WHEN "BULGES" DEVELOP IN THE SILT FENCE.




SEDIMENT & EROSION CONTROL MEASURES TYPICAL N.T.S.

- FOR RESIDENTIAL CONSTRUCTION, ONE SPECIFIC AREA ON EACH LOT SHALL BE DESIGNATED FOR TEMPORARY STOCKPILING OF TOPSOIL AND ALL OTHER CONSTRUCTION MATERIALS CONTAINING FINES THAT CAN BE MOVED BY RUNOFF. THIS AREA SHALL BE AS SMALL AS PRACTICABLE.
- STOCK PILES WILL HAVE DOWN HILL SIDE PERIMETER SILT FENCING PROTECTION. REFERENCE SILT FENCE DETAILS THESE PLANS.
- STOCK PILES WILL BE SEEDED AND MULCHED IF ANTICIPATED TO BE LEFT IN PLACE 14-DAYS OR MORE. REFERENCE DETAIL SHEET NOTES AND SPECIFICATIONS THIS PLAN SET AND STORMWATER POLLUTION PREVENTION PLAN (SWPPP) ACCOMPANYING THIS PLAN SET.
- SILT FENCE AND OTHER TEMPORARY CONTROL MEASURES SHALL BE IN PLACE BEFORE STOCKPILING OF MATERIALS.



CONSTRUCTION SPECIFICATIONS

- STONE WILL BE PLACED ON A FILTER FABRIC FOUNDATION TO THE LINES, GRADES AND LOCATIONS SHOWN IN THE PLAN.
- SET SPACING OF CHECK DAMS TO ASSUME THAT THE ELEVATIONS OF THE CREST OF THE DOWNSTREAM DAM IS AT THE SAME ELEVATION OF THE TOE OF THE UPSTREAM DAM.
- EXTEND THE STONE A MINIMUM OF 1.5 FEET BEYOND THE DITCH BANKS TO PREVENT CUTTING AROUND THE DAM.
- PROTECT THE CHANNEL DOWNSTREAM OF THE LOWEST CHECK DAM FROM SCOUR AND EROSION WITH STONE OR LINER AS APPROPRIATE.
- ENSURE THAT CHANNEL APPURTENANCES SUCH AS CULVERT ENTRANCES BELOW CHECK DAMS ARE NOT SUBJECT TO DAMAGE OR BLOCKAGE FROM DISPLACED STONE. MAXIMUM DRAINAGE AREA 2 ACRES.




CONSTRUCTION SPECIFICATIONS

- ALL TREES, BRUSH, STUMPS, OBSTRUCTIONS, AND OTHER OBJECTIONABLE MATERIAL SHALL BE REMOVED AND DISPOSED OF SO AS NOT TO INTERFERE WITH THE PROPER FUNCTIONING OF THE DIVERSION.
- THE DIVERSION SHALL BE EXCAVATED OR SHAPED TO LINE, GRADE, AND CROSS SECTION AS REQUIRED TO MEET THE CRITERIA SPECIFIED HEREIN, AND BE FREE OF BANK PROJECTIONS OR OTHER IRREGULARITIES WHICH WILL IMPED NORMAL FLOW.
- FILLS SHALL BE COMPACTED AS NEEDED TO PREVENT UNEQUAL SETTLEMENT THAT WOULD CAUSE DAMAGE IN THE COMPLETE DIVERSION.
- ALL EARTH REMOVED AND NOT NEEDED IN CONSTRUCTION SHALL BE SPREAD OR DISPOSED OF SO THAT IT WILL NOT INTERFERE WITH THE FUNCTIONING OF THE DIVERSION.
- STABILIZATION SHALL BE DONE ACCORDING TO THE APPROPRIATE STANDARD AND SPECIFICATIONS FOR VEGETATIVE PRACTICES.
 - FOR DESIGN VELOCITIES OF LESS THAN 3.5 FT. PER. SEC., SEEDING AND MULCHING MAY BE USED FOR THE ESTABLISHMENT OF THE VEGETATION. IT IS RECOMMENDED THAT, WHEN CONDITIONS PERMIT, TEMPORARY DIVERSIONS OR OTHER MEANS SHOULD BE USED TO PREVENT WATER FROM ENTERING THE DIVERSION DURING THE ESTABLISHMENT OF THE VEGETATION.
 - FOR DESIGN VELOCITIES OF MORE THAN 3.5 FT. PER. SEC., THE DIVERSION SHALL BE STABILIZED WITH SOD, WITH SEEDING PROTECTED BY JUTE OR EXCLESIOR MATTING OR WITH SEEDING AND MULCHING INCLUDING TEMPORARY DIVERSION OF THE WATER UNTIL THE VEGETATION IS ESTABLISHED.

No.	Date	SYML	REVISIONS
			Description

ESC DETAILS
 LEONIDAS GRP. OF VIRGIL, LLC
 5 SOUTH ST., PO BOX 1107
 CORTLANDVILLE (T) N. Y.
 DRYDEN, N.Y. 13053




TIMOTHY C. BUHL, P.E.
 GOODRICH HILL ROAD, LOCKE, N.Y. 13092 607 423-1919

DATE:	9-10-2018
SCALE:	N.T.S.
DRAWN:	MB/JLB
JOB:	17-14
SHEET:	


Q_f : 100-YR ("") EVENT
 BASIN PEAK VOL. = 74,296-CF, PEAK DEPTH = 10.04', EL. = 1156.04'
 Q_p : 10-YR ("") EVENT
 BASIN PEAK VOL. = 10,720-CF, PEAK DEPTH = 4.12', EL. = 1150.12'
 C_{pv} : 1-YR ("") EVENT
 BASIN PEAK VOL.* = 0.00-CF, PEAK DEPTH = 0.00', EL. = 0.00'

WQ_v : WATER QUALITY VOLUME* = 7,984-CF, DEPTH = 3.67', EL. = 1149.67'
 * - 50% calculated using zero exfiltration, saturated or frozen soil conditions.



Note 1: Use of recommended infiltration practices dependent upon successful NYSDEC standard infiltration rate testing with approval by The Town of Cortlandville and/or Cortland County. Test to be performed prior to issuance of any building permit. To be suitable for infiltration, underlying soils shall have an infiltration rate of at least 0.5"/hr, have a clay content of less than 20%, and have separation between the bottom of the treatment practice and the seasonal high groundwater table by at least 4 vertical feet.


Note 2: During the initial phase of construction, a sediment basin shall be established using the same footprint and surface area, as shown in these plans. A layer of Mirafi 140 N drainage fabric (or equal) shall be placed along the bottom of the basin to protect underlying soils from sediment during construction. Once soil disturbance has been completed and the site has achieved 80% germination, the basin shall be made permanent by removing the fabric, cleaning out all accumulated sediment, removing all compacted soil layers and then installing the engineered subgrade infiltration layers as shown in these plans.



FOREBAY PIPED OUTLETS
 (2) 18" CpEp
 81 LF @ S = 1.2% avg
 INV. EL. 1156'

REVISIONS	
No.	Description


INFILTRATION BASIN PLAN DETAILS
 LEONIDAS GRP. OF VIRGIL, LLC
 5 SOUTH ST., PO BOX 1107
 DRYDEN, N.Y. 13053




TIMOTHY C. BUHL, P.E.
 35 FIRELANE 24, AUBURN, N.Y. 13021 607 423-1919

DATE:	9-10-2018
SCALE:	N.T.S.
DRAWN:	MB/JLB
JOB:	17-14
SHEET:	ST-8

Infiltration Basin (Scale 1" = 20')




INFILTRATION BASIN OUTLET STRUCTURE DETAIL



CROSS-SECTION - BASIN


DIMENSIONS VARY AS PER PLAN



DETAIL- INFILTRATION BASIN SECTION - Typ.

NOTES ON INFILTRATION PRACTICES
 Note 1: During the initial phase of construction, a sediment trap shall be established using the same footprint and surface area, as shown in these plans. A layer of Mirafai 140 N drainage fabric (or equal) shall be placed along the bottom of the infiltration basin to protect underlying soils from sediment during construction. Once soil disturbance has been completed and the site has achieved 80% germination, the trap shall be converted to a full infiltration practice by removing the fabric, cleaning out all accumulated sediment and then installing the engineered subgrade infiltration layers as shown in these plans.

GENERAL PIPED OUTLETS, OVERFLOWS & CHANNEL DETAILS



- NOTES:**
 BASIN EMBANKMENT CONSTRUCTION:
 1. EMBANKMENT MATERIAL SPECIFICATIONS: EMBANKMENT CORE AND CUT OFF TRENCH MATERIAL SHALL BE MATERIAL CONFORMING TO UNIFIED SOIL CLASSIFICATION CL, SC, CH, OR CL WITH AT LEAST JOE PASSING #200 SIEVE. CORE AND CUT OFF TRENCH MATERIAL SHALL BE STOCKPILED SEPARATELY FROM OTHER SOIL MATERIAL. MATERIAL SHALL BE FREE OF ROOTS, STUMPS, WOOD, RUBBISH, STONES GREATER THAN 6-INCHES, FROTH OR OTHER OBJECTIONABLE MATERIALS. STOCKPILED MATERIAL SHALL BE COVERED AND PROTECTED FROM WATER, TRAFFIC AND OTHER DELETERIOUS SUBSTANCES OR PROCESSES.
 2. EMBANKMENT COMPACTION: EMBANKMENT FILL SHALL BE PLACED IN 12-INCH LIFTS MAXIMUM AND COMPACTED. THE MINIMUM REQUIRED DENSITY SHALL NOT BE LESS THAN 95% OF MAXIMUM DRY DENSITY WITH A MOISTURE CONTENT WITHIN 2% OF OPTIMUM. ALL COMPACTION TO BE DETERMINED BY ASTM METHOD 99 STANDARD PROCTOR.
 3. EMBANKMENT CORE DIMENSIONS: THE CORE SHALL BE PARALLEL TO THE CENTERLINE OF THE EMBANKMENT AS SHOWN ON THE PLANS. THE TOP WIDTH OF THE CORE SHALL BE A MINIMUM OF FOUR FEET. THE HEIGHT SHALL EXTEND UP AT LEAST THE 10 YEAR WATER ELEVATION OR AS SHOWN ON THE PLANS. THE SIDE SLOPES SHALL BE 1 TO 1 OR FLATTER. THE CORE SHALL BE COMPACTED WITH CONSTRUCTION COMPACTION EQUIPMENT: ROLLERS, OR TAMPS TO ASSURE MAXIMUM DENSITY AND MINIMUM PERMEABILITY. THE CORE SHALL BE CONSTRUCTED/PLACED CONCURRENTLY WITH THE OUTER SHELL OF THE EMBANKMENT.
 4. EMBANKMENT SURFACE: A 4-INCH LAYER OF TOPSOIL SHALL BE PLACED ON ENTIRE SURFACE AREA OF THE EMBANKMENT. GOOD GRASSED COVER SHALL BE ESTABLISHED BY SEEDING, LAMING, FERTILIZING, MULCHING, ETC. IN ACCORDANCE WITH NEW YORK STATE STANDARDS AND SPECIFICATIONS FOR SOIL EROSION AND SEDIMENT CONTROL. EMBANKMENT SHALL BE KEPT FREE OF WOODY PLANT GROWTH AND TREES.

STONE LINING FOR STORMWATER CONVEYANCE SECTIONS

MIN THICKNESS (INCHES)	STONE FILLING ITEM	V MAX #2 2' DEPTH	SEE NOTES	STONE SIZE*	PERCENT OF TOTAL BT WEIGHT	MANNING'S ROUGHNESS COEFFICIENT
9"	FINE	11.0 PPS	2,3,4	SMALLER THAN #4* LARGER THAN #10 SMALLER THAN NO. 10 SIEVE	90-100 50-100 0-10	0.0314
15"	LIGHT	13.0 PPS	2,3,4	LIGHTER THAN 100 LBS LARGER THAN #4* SMALLER THAN 1/2"	90-100 50-100 0-10	0.0352
18"	MEDIUM	15.5 PPS	2,3,4	HEAVIER THAN 100 LBS SMALLER THAN 4"	90-100 50-100 0-10	0.0395
30"	HEAVY	17.0 PPS	2,3,4	HEAVIER THAN 100 LBS SMALLER THAN 6"	90-100 50-100 0-10	0.0423


- *1 SOURCE: HYDRAULIC ENGINEERING CIRCULAR NO. 15 DESIGN OF STABLE CHANNELS WITH FLEXIBLE LININGS
 *2 SOURCE: SOILS DESIGN PROCEDURE SDP2, BANK AND CHANNEL PROTECTIVE LINING DESIGN PROCEDURES
NOTES:
 1. STONE SIZES, OTHER THAN WEIGHTS, REFER TO THE AVERAGE OF THE MAXIMUM AND MINIMUM DIMENSIONS OF A STONE PARTICLE AS ESTIMATED BY THE ENGINEER.
 2. MATERIALS SHALL CONTAIN LESS THAN 20 PERCENT OF STONES WITH A RATIO OF MAXIMUM TO MINIMUM DIMENSIONS GREATER THAN THREE.
 3. AIR-COOLED BLAST FURNACE SLAG, COBBLES OR GRAVEL HAVING AT LEAST ONE FRACTURED FACE PER ACCESSIBLE SUBSTITUTES FOR STONE UNDER THESE ITEMS, PROVIDED THAT SOUNDNESS AND GRADATION REQUIREMENTS ARE MET.
 4. MATERIALS SHALL CONTAIN A SUFFICIENT AMOUNT OF STONES SMALLER THAN THE AVERAGE STONE SIZE TO FILL THE SPACES BETWEEN THE STONES.

TYPICAL OUTLET, OVERFLOW, AND CHANNEL DETAILS
 REFERENCE THE BASIN PLAN & SECTION SHEETS FOR ELEVATIONS, DIMENSIONS, LINES & GRADES

REVISIONS



No.	Date	SYMBOL	Description

INFILTRATION BASIN SECTION
 LEONIDAS GRP. OF VIRGIL, LLC
 5 SOUTH ST.-PO BOX 1107
 DRYDEN, N.Y. 13053
 STARR RD. RESIDENTIAL PUD
 STARR ROAD
 CORTLANDVILLE (T) N.Y.





TIMOTHY C. BUHL, P.E.
 35 FIRELANE 24, AUBURN, N.Y. 13021 607 423-1919

DATE: 9-10-2018
 SCALE: N.T.S.
 DRAWN: MB/JLB
 JOB: 17-14
 SHEET: ST-9



Bioretention Area Details				
Location	Bottom Length (ft)	Bottom Width (ft)	Bottom Surface Area (Sqft)	Floor of Practice El. (ft)
Bioretention Area 1	133	8	1068	1235.0
Bioretention Area 2	182	8	1446	1227.0
Bioretention Area 3	92	12	1156	1211.0
Bioretention Area 4	69	10	682	1201.0
Bioretention Area 5	69	10	682	1195.0


Bioretention Suggested Plantings - USDA Zone 5A	
SHRUBS	HERBACEOUS PLANTS
Witch Hazel <i>Hamamelis virginiana</i>	Cinnamon Fern <i>Osmunda cinnamomea</i>
Winterberry <i>Ilex verticillata</i>	Cutleaf Coneflower <i>Rudbeckia laciniata</i>
Arrowwood <i>Viburnum dentatum</i>	Woolgrass <i>Scirpus cyperinus</i>
Brook-side Alder <i>Alnus serrulata</i>	New England Aster <i>Aster novae-angliae</i>
Red-Osier Dogwood <i>Cornus stolonifera</i>	Fox Sedge <i>Carex vulpinoidea</i>
Sweet Pepperbush <i>Clethra alrifolia</i>	Spotted Joe-Pye Weed <i>Eupatorium maculatum</i>
	Switch Grass <i>Panicum virgatum</i>
	Great Blue Lobelia <i>Lobelia siphatica</i>
	Wild Bergamot <i>Mondarda fistulosa</i>
	Red Milkweed <i>Asclepias incarnata</i>



NOTES ON INFILTRATION PRACTICES
 Note 1: During the initial phase of construction, sediment traps shall be established using the same footprint AND surface area, as shown in these plans. A layer of Mirafi 140 N drainage fabric (or equal) shall be placed along the bottom of the traps to protect underlying soils from sediment during construction. Once soil disturbance has been completed and the site has achieved 80% germination, the traps shall be converted to bioretention areas by removing the fabric, cleaning out all accumulated sediment and then installing the engineered subgrade infiltration layers as shown in these plans.

SPECIFICATIONS FOR BIORETENTION SYSTEMS
Planting Soil
 The soil shall be a uniform mix, free of stones, stumps, roots or other similar objects larger than two inches. No other materials or substances shall be mixed or dumped within the bioretention area that may be harmful to plant growth, or prove a hindrance to the planting or maintenance operations. The planting soil shall be free of noxious weeds.
Planting soil shall be of a sandy loam consistency containing approximately 35-60% sand, 30-55% silt, and 10-25% clay.
Compaction
 Minimize compaction of both the base of the bioretention area and the required backfill. Place soil in lifts 12" or great. Do not use heavy equipment within the bioretention area basin.

CONSTRUCTION PHASE SEQUENCE
 A. Construction of stabilized construction egress(es);
 B. Placement of silt fence;
 C. Construction of infiltration basin and associated swales as necessary to bring runoff into practice from areas as shown on design plans ST-15.
 D. Construct bioretention areas and/or rain gardens downslope of anticipated areas of disturbance in a sequence following the construction schedule. For instance, in anticipation of building construction in Subcatchment PSC-6, Bioretention Area 2 must first be constructed to capture and treat runoff generated from that area.
 E. Construction of development roadway to gain access to each individual construction area.
 F. Construction of the development of buildings and associated driveway/parking area:
 a. Construct driveways and individual lot temporary parking;
 b. Construct general utility services (ie. water and sewer piping, storm piping, etc.)
 c. Construct buildings;
 d. Construct other utility service connections (gas, electric, phone);
 Note: For all Underground Utilities Sediment barriers will be utilized as required to bind the down slope side of utility construction and soil stockpiles;
 G. Remove any accumulated sedimentation from bioretention areas, rain gardens, forebays, general infiltration basins and associated swales. Return property to permanent lines and grades; refer to detailed notes on sheets ST-8 and ST-10;
 H. Final Grading Mulching & Seeding 1 Sediment barriers will be maintained down slope from disturbed soil during these operations;
 I. Completion of site stabilization, ie. Vegetative cover, driveway surface. Sediment & Erosion Controls to remain in place until vegetative cover reaches 80% density.



REVISIONS Description

No. Date SYM

BIORETENTION AREA DETAILS 2

LEONIDAS GRP. OF VIRGIL, LLC
 5 SOUTH ST., PO BOX 1107
 DRYDEN, N.Y. 13053

STARR RD. RESIDENTIAL PUD
 STARR ROAD
 CORTLANDVILLE (T) N. Y.

STATE OF NEW YORK
 PROFESSIONAL ENGINEER
 LICENSE NO. 13021

TIMOTHY C. BUHL, P.E.

35 FIRELANE 24, AUBURN, N.Y. 13021 607423-1919

DATE: 9-10-2018
 SCALE: N.T.S.
 DRAWN: MB/JLB
 JOB: 17-14
 SHEET: ST-10

Section 9.5.1 Alternative Stormwater Management Practices Rain Gardens

Description

The rain garden is a stormwater management practice to manage and treat small volumes of stormwater runoff using a conditioned planting soil bed and planting materials to filter runoff stored within a shallow depression. They are most commonly used in residential land use settings. The method is a variation on bioretention and combines physical filtering and adsorption with bio-geochemical processes to remove pollutants. Rain gardens are typically smaller than bioretention and are generally designed as a more passive filter system without an underdrain connected to the stormdrain system, although a gravel filter bed is recommended. Rainwater is directed into the garden from residential roof drains, driveways and other hard surfaces. The runoff temporarily ponds in the garden and seeps into the soil over several days. The system consists of an inflow component, a shallow ponding area over a planted soil bed, a mulch layer, a gravel filter chamber, plant materials consisting of attractive shrubs, grasses and flowers, and an overflow mechanism to convey larger rain events to the storm drain system (see Figure 1) or receiving waters.



Figure 1: Layout of a typical rain garden

Recommended Application of the Practice

The rain garden is suitable for townhouse and single family residential applications where it is used to treat small storm runoff from residential rooftops, driveways, and sidewalks. Rain gardens can be utilized in residential redevelopment projects, including townhouse projects, and in some institutional settings such as schoolyard projects. Since rain gardens do not need to be tied directly into the stormdrain system, they can be used to treat areas that may be difficult to otherwise address due to inadequate head or other grading issues. Rain gardens are designed as an "exfilter," allowing rainwater to slowly seep through the soil. They have a prepared soil mix and should be designed with a deeper gravel chamber to improve treatment volume, and to compensate for clays and fines washing into the area. They are typically 150 - 300 square feet for a residential area. Rain gardens can be integrated into a site with a high degree of flexibility and work well in combination with other structural management systems, including porous pavement, infiltration trenches, and swales.

Benefits

Rain gardens can have many benefits when applied to redevelopment and infill projects in urban settings. The most notable include:

- Effective pollutant treatment for residential rooftops and driveways, including solids, metals, nutrients and hydrocarbons
- Groundwater recharge augmentation
- Micro-scale habitat
- Aesthetic improvement to turfgrass or otherwise hard urban surfaces (Figure 2)
- Ease of maintenance, coupling routine landscaping maintenance with effective stormwater management control
- Promotion of watershed education and stewardship




Figure 2: Rain gardens also have aesthetic value.

Feasibility/Limitations

Rain gardens have some limitations, similar to bioretention, that restrict their application. The most notable of these include:

- Steep slopes. Rain gardens require relatively flat slopes to be able to accommodate runoff filtering through the system. Some design modifications can address this constraint through the use of berms and timber or block retaining walls on moderate slopes.
- Compacted and clay soils. Soils compacted by construction and heavy clay soils need more augmentation than sandy soils, though all soils should be prepared to specification. In compacted soils and clay, additional excavation is necessary, along with a gravel bed and, under some circumstances, an underdrain system.

- A single rain garden system should be designed to receive sheet flow runoff or shallow concentrated flow from an impervious area or from a roof drain downspout with a drainage area equal to or less than 1,000 square feet. Because the system works by filtration through a planting media, runoff must enter at the surface.
- The rain garden must be sited in a location that allows overflow from the area to sheet flow or be otherwise safely conveyed to the formal drainage system. Rain gardens should be located downgradient and at least 10 feet from basement foundations.
- Rain gardens require a modest land area to effectively capture and treat residential runoff from storms up to approximately the 1-inch precipitation event.
- Rain gardens should not be located in areas with heavy tree cover, as the root systems will make installation difficult and may be damaged by the excavation.

Sizing and Design Guidance

Stormwater quantity reduction in rain gardens occurs via evaporation, transpiration, and infiltration, though only the infiltration capacity of the soil and drainage system is considered for water quality sizing. The storage volume of a rain garden is achieved within the gravel bed, soil medium and ponding area above the bed. The size should be determined using the water quality volume (WQv), where the site area is the impervious area draining to the rain garden. The following sizing criteria should be followed to arrive at the surface area of the rain garden, based on the required WQv:

$$WQv \leq V_{SM} + V_{DL} + (D_p \times ARG)$$

$$V_{SM} = ARG \times D_{SM} \times \rho_{SM}$$

$$V_{DL} (\text{optional}) = ARG \times D_{DL} \times \rho_{DL}$$

where:

V_{SM} = volume of the soil media [cubic feet]

V_{DL} = volume of the drainage layer [cubic feet]

ARG = rain garden surface area [square feet]

D_{SM} = depth of the soil media, typically 1.0 to 1.5 feet [feet]

D_{DL} = depth of the drainage layer, typically .05 to 1.0 feet [feet]

D_p = depth of ponding above surface, maximum 0.5 feet [feet]

ρ_{SM} = porosity of the soil media ($\geq 20\%$)

ρ_{DL} = porosity of the drainage layer ($\geq 40\%$)

WQv = Water Quality Volume [cubic feet], as defined in Chapter 4 of the New York Stormwater Management Design Manual

A simple example for sizing rain gardens based upon WQv is presented in Table 1.

Table 1: Rain Garden Simple Sizing Example

Given a 1,000 square foot impervious drainage area (e.g., rooftop), a rain garden design has been proposed with a 200 square foot surface area, a soil layer depth of 12 inches, a drainage layer depth of 6 inches, and an allowable ponding depth of 3 inches. Evaluate if the proposed rain garden design satisfies site WQv requirements

Step 1: Calculate water quality volume using the following equation:

$$WQv = \frac{(P)(Rv)(A)}{12}$$

where:

$$P = 90\% \text{ rainfall number} = 0.9 \text{ in}$$

$$Rv = 0.05 + 0.009(I) = 0.05 + 0.009(100) = 0.95$$

I = Percentage impervious area draining to site = 100%

A = Area draining to practice (treatment area) = 1,000 ft²

$$WQv = \frac{(0.9)(0.95)(1,000)}{12} \quad WQv = 71.25 \text{ ft}^3$$

Step 2: Solve for drainage layer and soil media storage volume:

$$V_{SM} = ARG \times D_{SM} \times \rho_{SM}$$

$$V_{DL} = ARG \times D_{DL} \times \rho_{DL}$$

where:

ARG = proposed rain garden surface area = 200 ft²

D_{SM} = depth soil media = 12 inches = 1.0 ft

D_{DL} = depth drainage layer = 6 inches = 0.5 ft

ρ_{SM} = porosity of soil media = 0.20

ρ_{DL} = porosity of drainage layer = 0.40

$$V_{SM} = 200 \text{ ft}^2 \times 1.0 \text{ ft} \times 0.20 = 40 \text{ ft}^3$$

$$V_{DL} = 200 \text{ ft}^2 \times 0.5 \text{ ft} \times 0.40 = 40 \text{ ft}^3$$

D_p = ponding depth = 3 inches = 0.25 ft

$$WQv \leq V_{SM} + V_{DL} + (D_p \times ARG) = 40 \text{ ft}^3 + 40 \text{ ft}^3 + (0.25 \text{ ft} \times 200 \text{ ft}^2)$$

$$WQv = 71.25 \text{ ft}^3 \leq 130.0 \text{ ft}^3, \text{ OK}$$

Therefore, the proposed design for treating an area of 1,000 ft² satisfies the WQv requirements.

Siting Rain gardens should be located within approximately 30 feet of the downspout or impervious area treated. Rooftop conveyance to the rain garden is through roof leaders directed to the area, with stone or splash blocks placed at the point of discharge into the rain garden to prevent erosion. Runoff from driveways and other paved surfaces should be directed to the rain garden at a non-erosive rate through shallow swales, or allowed to sheet flow across short distances (Figure 3).

Sizing The following considerations should be given to design of the rain garden (after PA Stormwater Design Manual, Bannerman 2003 and LID Center):



Figure 3: This rain garden treats road and driveway runoff.

- Ponding depth above the rain garden bed should not exceed 6 inches. The recommended maximum ponding depth of 6 inches provides surface storage of stormwater runoff, but is not too deep to affect plant health, safety, or create an environment of stagnant conditions. On perfectly flat sites, this depth is achieved through excavation of the rain garden and backfilling to the appropriate level; on sloping sites, this depth can be achieved with the use of a berm on the downslope edge, and excavation/backfill to the required level.
- Surface area is dependent upon storage volume requirements but should not exceed a maximum loading ratio of 5:1 (drainage area to infiltration area, where drainage area is assumed to be 100% impervious; to the extent that the drainage area is not 100% impervious, the loading ratio may be modified)
- A length to width ratio of 2:1, with the long axis perpendicular to the slope and flow path is recommended.

Soil The composition of the soil media should consist of 50% sand, 20-30% topsoil with less than 5% clay content, and 20-30% leaf compost. The depth of the amended soil should be approximately 4 inches below the bottom of the deepest root ball.

Construction Rain gardens should initially be dug out to a 24" depth, then backfilled with a 6 - 10 inch layer of clean washed gravel (approximately 1.5-2.0 inch diameter rock), and filled back to the rain garden bed depth with a certified soil mix.


Table 2: Suggested Plant List

Shrubs	Herbaceous Plants
Witch Hazel	Cinnamon Fern
Hamamelis virginiana	Osmunda cinnamomea
Winterberry	Cutleaf Coneflower
Ilex verticillata	Rudbeckia laciniata
Airrowood	Woolgrass
Viburnum dentatum	Scirpus cyperinus
Brook-side Alder	New England Aster
Alnus serrulata	Aster novae-angliae
Red-Osier Dogwood	Fox Sedge
Cornus stolonifera	Carex vulpinoidea
Sweet Pepperbush	Spotted Joe-Pye Weed
Clethra alnifolia	Eupatorium maculatum
	Switch Grass
	Panicum virgatum
	Great Blue Lobelia
	Lobelia siphatica
	Wild Bergamot
	Monarda fistulosa
	Red Milkweed
	Asclepias incarnata


Adapted from NYSM Bioretention Specifications, Bannerman, Brooklyn Botanic Garden.

Maintenance

Rain gardens are intended to be relatively low maintenance. Weeding and watering are essential the first year, and can be minimized with the use of a weed free mulch layer. Rain gardens should be treated as a component of the landscaping, with routine maintenance provided by the homeowner or homeowners' association, including the occasional replacement of plants, mulching, weeding and thinning to maintain the desired appearance. Homeowners and landscapers should be educated regarding the purpose of the rain garden, so the desirable aspects of ponded water are recognized and maintained.




DETAIL - PLAN RAIN GARDEN W/ UNDERDRAIN SYSTEM (Typ.)



DETAIL - CROSS SECTION RAIN GARDEN W/ UNDERDRAIN SYSTEM


REVISIONS	Description	No.	Date	SYMBOL

TYPICAL RAIN GARDEN DETAILS
 LEONIDAS GRP. OF VIRGIL, LLC
 5 SOUTH ST., PO BOX 1107
 CORTLANDVILLE (T) N.Y.
 DRYDEN, N.Y. 13053



TIMOTHY C. BUHL, P.E.
 35 FIRELANE 24, AUBURN, N.Y. 13021 607-423-1919

DATE: 9-10-2018
SCALE: N.T.S.
DRAWN: MB/JLB
JOB: 17-14
SHEET:



Existing Subcatchment - 1 (ESC-1)
 Existing Conditions - Area = 900,759-SF (20.68-AC)

Surface Conditions & Soils:
 9.7% 125A & 125B, Howard, Hydrologic Soil Group (HSG) A
 48% 107B, Conesus; 108B, Lansing; 53C & 53D, Valois-Howard, Hydrologic Soil Group (HSG) B
 42.3% 63B, Mardin, Hydrologic Soil Group (HSG) D

Runoff Curve Number = 79, Woodland/Grass Combination, HSG D Soils
 Runoff Curve Number = 58, Woodland/Grass Combination, HSG B Soils
 Runoff Curve Number = 32, Woodland/Grass Combination, HSG A Soils
 Runoff Curve Number = 30, Brush, HSG A Soils
 Runoff Curve Number = 48, Brush, HSG B Soils

Overland Stormwater Runoff - Longest Flowpath = 3,477lf +/-
 Sheet Flow, Woods/Dense Underbrush - 150 LF @ S = 8.0% avg +/-
 Shallow Conc. Flow, Woodland - 2,411 LF @ S = 10.4% avg +/-
 Shallow Conc. Flow, Short Grass Pasture - 440 LF @ S = 10.7% avg +/-
 Trap/Vee Channel Flow - 476 LF @ S = 9.0% avg +/-

To - (DP 1)

ESC-1
 20.68AC

REFERENCE HYDROCAD (HYDRAULIC & HYDROLOGIC) MODELING RESULTS PRESENTED WITH THESE PLANS
 EXISTING CONDITIONS


No.	Date	SYM.	REVISIONS Description

HYDROLOGIC AND HYDRAULIC
 WORKSHEET - EXISTING COND.
 LEONIDAS GRP. OF VIRGIL, LLC
 5 SOUTH ST., PO BOX 1107
 DRYDEN, N.Y. 13053



TIMOTHY C. BUHL, P.E.
 35 FIRELANE 24, AUBURN, N.Y. 13021 607 423 1919

DATE:	9-10-2018
SCALE:	N.T.S.
DRAWN:	MB/JLB
JOB:	17-14
SHEET:	ST-12



Off-Site Subcatchment - 1 (OSC-1)
 Proposed Conditions - Area = 383,171SF (8.80-AC)

Surface Conditions & Soils:
 100.0% 63B, Mardin, Hydrologic Soil Group (HSG) D

Runoff Curve Number = 79, Woodland/Grass Combination, HSG D Soils

Overland Stormwater Runoff - Longest Flowpath = 2,768 lf +/-
 Sheet Flow, Woods/Dense Underbrush - 150 LF @ S = 8.0% avg +/-
 Shallow Conc. Flow, Woodland - 2,350LF @ S = 10.4% avg +/-
 Trap/Vee Channel Flow - 268LF @ S = 6.0% avg +/-

To - (DP 1)

Off-Site Subcatchment - 2 (OSC-2)
 Proposed Conditions - Area = 22,679 SF (0.52-AC)

Surface Conditions & Soils:
 37% 63B, Mardin, Hydrologic Soil Group (HSG) D
 63% 108B, Lansing ; Hydrologic Soil Group (HSG) B

Runoff Curve Number = 79, Woodland/Grass Combination, HSG D Soils
 Runoff Curve Number = 48, Brush, HSG B Soils

Overland Stormwater Runoff - Longest Flowpath = 709 lf +/-
 Sheet Flow, Woods/Dense Underbrush - 100 LF @ S = 8.0% avg +/-
 Trap/Vee Channel Flow - 609LF @ S = 7.6% avg +/-

To - (DP 1)


OSC-1
8.80-AC

OSC-2
0.52-AC

DP - 1

REFERENCE HYDROCAD (HYDRAULIC & HYDROLOGIC) MODELING RESULTS PRESENTED WITH THESE PLANS
 PROPOSED OFF-SITE WATERSHED CONDITIONS

REVISIONS	
No.	Date / SYM.
HYDROLOGIC AND HYDRAULIC WORKSHEET - PROPOSED COND. 1 STARR RD. RESIDENTIAL PUD STARR ROAD CORTLANDVILLE (T) N.Y.	
LEONIDAS GRP. OF VIRGIL, LLC 5 SOUTH ST., PO BOX 1107 DRYDEN, N.Y. 13053	
TIMOTHY C. BUHL, P.E. 35 FIRELANE 24, AUBURN, N.Y. 13021 607423-1919	
DATE:	9-10-2018
SCALE:	N.T.S.
DRAWN:	MB/JLB
JOB:	17-14
SHEET:	ST-13



Proposed Subcatchment - 1 (PSC-1)
 Proposed Conditions - Area = 20,935 SF (0.48-AC)

Surface Conditions & Soils:
 9% 63B, Mardin, Hydrologic Soil Group (HSG) D
 91% 108B, Lansing; Hydrologic Soil Group (HSG) B

Runoff Curve Number = 98, Rooftops/Impervious
 Runoff Curve Number = 73, Dense Grass, HSG D Soils
 Runoff Curve Number = 61, Grass Cover >75%, HSG B Soils

Overland Stormwater Runoff - Longest Flowpath = 271 lf +/-
 Sheet Flow - Dense Grass, 100 LF @ S = 9.0% avg +/-
 Shallow Conc. Flow - Grassed Waterway, 171LF @ S = 5.3% avg +/-

To - (DP 1)

Proposed Subcatchment - 2 (PSC-2)
 Proposed Conditions - Area = 15,616 SF (0.36-AC)

Surface Conditions & Soils:
 39% 63B, Mardin, Hydrologic Soil Group (HSG) D
 61% 108B, Lansing; Hydrologic Soil Group (HSG) B

Runoff Curve Number = 98, Rooftops/Impervious
 Runoff Curve Number = 73, Brush, HSG D Soils
 Runoff Curve Number = 61, Grass Cover >75%, HSG B Soils

Overland Stormwater Runoff - Longest Flowpath = 114 lf +/-
 Sheet Flow - Short Grass, 100 LF @ S = 9.5% avg +/-
 Shallow Conc. Flow - Grassed Waterway, 14LF @ S = 6% avg +/-

To - (DP 1)

Proposed Subcatchment - 3 (PSC-3)
 Proposed Conditions - Area = 25,151 SF (0.58-AC)

Surface Conditions & Soils:
 0.5% 63B, Mardin, Hydrologic Soil Group (HSG) D
 99.5% 107B, Conesus; 108B, Lansing; Hydrologic Soil Group (HSG) B

Runoff Curve Number = 98, Rooftops/Impervious
 Runoff Curve Number = 80, Grass Cover >75%, HSG D Soils
 Runoff Curve Number = 61, Grass Cover >75%, HSG B Soils

Overland Stormwater Runoff - Longest Flowpath = 165 lf +/-
 Sheet Flow - Short Grass, 100 LF @ S = 9.5% avg +/-
 Shallow Conc. Flow - Grassed Waterway, 65LF @ S = 7.7% avg +/-

To - (DP 1)

Proposed Subcatchment - 4 (PSC-4)
 Proposed Conditions - Area = 8,943 SF (0.21-AC)

Surface Conditions & Soils:
 100% 107B, Conesus; Hydrologic Soil Group (HSG) B

Runoff Curve Number = 98, Rooftops/Impervious
 Runoff Curve Number = 61, Grass Cover >75%, HSG B Soils

Overland Stormwater Runoff - Longest Flowpath = 82 lf +/-
 Sheet Flow - Short Grass, 100 LF @ S = 7.0% avg +/-

To - (DP 1)

Proposed Subcatchment - 5 (PSC-5)
 Proposed Conditions - Area = 12,665 SF (0.29-AC)

Surface Conditions & Soils:
 100% 107B, Conesus; Hydrologic Soil Group (HSG) B

Runoff Curve Number = 98, Rooftops/Impervious
 Runoff Curve Number = 61, Grass Cover >75%, HSG B Soils

Overland Stormwater Runoff - Longest Flowpath = 115 lf +/-
 Sheet Flow - Short Grass, 51 LF @ S = 8.8% avg +/-
 Sheet Flow - Smooth Surfaces, 25 LF @ S = 1.0% avg +/-
 Sheet Flow - Short Grass, 24 LF @ S = 4.0% avg +/-
 Shallow Conc. Flow - Grassed Waterway, 15 LF @ S = 5.0% avg +/-

To - (DP 1)

Proposed Subcatchment - 6 (PSC-6)
 Proposed Conditions - Area = 29,924 SF (0.69-AC)

Surface Conditions & Soils:
 100% 107B, Conesus; 108B, Lansing; Hydrologic Soil Group (HSG) B

Runoff Curve Number = 98, Rooftops/Impervious
 Runoff Curve Number = 61, Grass Cover >75%, HSG B Soils

Overland Stormwater Runoff - Longest Flowpath = 152 lf +/-
 Sheet Flow - Short Grass, 90 LF @ S = 12.2% avg +/-
 Shallow Conc. Flow - Pavement, 62LF @ S = 4.8% avg +/-

To - (DP 1)

Proposed Subcatchment - 10 (PSC-10)
 Proposed Conditions - Area = 20,980SF (0.48-AC)

Surface Conditions & Soils:
 100% 108B, Lansing; Hydrologic Soil Group (HSG) B

Runoff Curve Number = 98, Rooftops/Impervious
 Runoff Curve Number = 61, Grass Cover >75%, HSG B Soils

Overland Stormwater Runoff - Longest Flowpath = 233 lf +/-
 Sheet Flow - Short Grass, 77 LF @ S = 18.1% avg +/-
 Sheet Flow - Smooth Surfaces 23 LF @ S = 4.0% avg +/-
 Shallow Conc. Flow - Paved, 54 LF @ S = 3.7% avg +/-
 Shallow Conc. Flow - Grassed Waterway, 79LF @ S = 15.1% avg +/-

To - (DP 1)

Proposed Subcatchment - 11 (PSC-11)
 Proposed Conditions - Area = 10,429 SF (0.24-AC)

Surface Conditions & Soils:
 100% 53C and D, Valois-Howard; Hydrologic Soil Group (HSG) B

Runoff Curve Number = 98, Rooftops/Impervious
 Runoff Curve Number = 61, Grass Cover >75%, HSG B Soils

Overland Stormwater Runoff - Longest Flowpath = 153 lf +/-
 Sheet Flow - Short Grass, 94 LF @ S = 10.6% avg +/-
 Shallow Conc. Flow - Paved, 37 LF @ S = 8.1% avg +/-
 Shallow Conc. Flow - Grassed Waterway, 22LF @ S = 13.6% avg +/-

To - (DP 1)

Proposed Subcatchment - 12 (PSC-12)
 Proposed Conditions - Area = 22,163 SF (0.51-AC)

Surface Conditions & Soils:
 100% 53D, Valois-Howard; 107B, Conesus; 108B, Lansing; Hydrologic Soil Group (HSG) B

Runoff Curve Number = 98, Rooftops/Impervious
 Runoff Curve Number = 61, Grass Cover >75%, HSG B Soils

Overland Stormwater Runoff - Longest Flowpath = 185 lf +/-
 Sheet Flow - Short Grass, 94 LF @ S = 10.6% avg +/-
 Shallow Conc. Flow - Paved, 50 LF @ S = 4.0% avg +/-
 Shallow Conc. Flow - Grassed Waterway, 41LF @ S = 9.7% avg +/-

To - (DP 1)

Proposed Subcatchment - 7 (PSC-7)
 Proposed Conditions - Area = 11,807 SF (0.27-AC)

Surface Conditions & Soils:
 100% 107B, Conesus; Hydrologic Soil Group (HSG) B

Runoff Curve Number = 98, Rooftops/Impervious
 Runoff Curve Number = 61, Grass Cover >75%, HSG B Soils

Overland Stormwater Runoff - Longest Flowpath = 137 lf +/-
 Sheet Flow - Short Grass, 60 LF @ S = 8.3% avg +/-
 Sheet Flow - Smooth Surfaces, 29 LF @ S = 1.0% avg +/-
 Sheet Flow - Short Grass, 11 LF @ S = 20.0% avg +/-
 Shallow Conc. Flow - Grassed Waterway 37LF @ S = 8.1% avg +/-

To - (DP 1)

Proposed Subcatchment - 8 (PSC-8)
 Proposed Conditions - Area = 31,189 SF (0.72-AC)

Surface Conditions & Soils:
 100% 107B, Conesus; 108B, Lansing; Hydrologic Soil Group (HSG) B

Runoff Curve Number = 98, Rooftops/Impervious
 Runoff Curve Number = 61, Grass Cover >75%, HSG B Soils

Overland Stormwater Runoff - Longest Flowpath = 174 lf +/-
 Sheet Flow - Short Grass, 77 LF @ S = 18.1% avg +/-
 Sheet Flow - Smooth Surfaces, 23 LF @ S = 1.0% avg +/-
 Shallow Conc. Flow - Paved 74F @ S = 2.0avg +/-

To - (DP 1)


Proposed Subcatchment - 9 (PSC-9)
 Proposed Conditions - Area = 10,873SF (0.25-AC)

Surface Conditions & Soils:
 100% 107B, Conesus; 108B, Lansing; Hydrologic Soil Group (HSG) B

Runoff Curve Number = 98, Rooftops/Impervious
 Runoff Curve Number = 61, Grass Cover >75%, HSG B Soils


Overland Stormwater Runoff - Longest Flowpath = 177 lf +/-
 Sheet Flow - Short Grass, 100 LF @ S = 6.0% avg +/-
 Shallow Conc. Flow - Paved 29LF @ S = 6.9% avg +/-
 Shallow Conc. Flow - Grassed Waterway, 48 LF @ S = 8.3% avg +/-

To - (DP 1)



REFERENCE HYDROCAD (HYDRAULIC & HYDROLOGIC) MODELING RESULTS PRESENTED WITH THESE PLANS
 PROPOSED ON-SITE CONDITIONS

REVISIONS	
No.	Date / SYM / Description
HYDROLOGIC AND HYDRAULIC WORKSHEET - PROPOSED COND. 2	
LEONIDAS GRP. OF VIRGIL, LLC	5 SOUTH ST.-PO BOX 1107
DRYDEN, N.Y. 13053	
STARR ROAD	CORTLANDVILLE (T) N.Y.
TIMOTHY C. BUHL, P.E.	
35 FIRELANE24, AUBURN, N.Y. 13021 607-423-1919	
DATE: 9-10-2018	SCALE: N.T.S.
DRAWN: MB/JLB	JOB: 17-14
SHEET: ST-14	



Proposed Subcatchment - 13 (PSC-13)
 Proposed Conditions - Area = 113,779-SF (2.61AC)

Surface Conditions & Soils:
 20% 125A & 125B, Howard, Hydrologic Soil Group (HSG) A
 80% 107B, Conesus; 108B, Lansing; 53C & 53D,
 Valois-Howard, Hydrologic Soil Group (HSG) B

Runoff Curve Number = 61, >75% Grass, HSG B Soils
 Runoff Curve Number = 39, >75% Grass, HSG A Soils
 Runoff Curve Number = 98, Impervious, HSG A Soils
 Runoff Curve Number = 98, Impervious, HSG B Soils

Overland Stormwater Runoff - Longest Flowpath = 1,100lf +/-
 Sheet Flow, Short Grass - 100 LF @ S = 5.0% avg +/-
 Shallow Conc. Flow, Grassed Waterway - 112 LF @ S = 8.0% avg +/-
 Shallow Conc. Flow, Grassed Waterway - 37 LF @ S = 13.5% avg +/-
 Trap/Vee Channel Flow - 107 LF @ S = 11.2% avg +/-
 Circular Pipe 15" - 54 LF @ S = 5.5% avg +/-
 Trap/Vee Channel Flow - 155LF @ S = 8.4% avg +/-
 Circular Pipe 18" - 48 LF @ S = 10.4% avg +/-
 Trap/Vee Channel Flow - 290 LF @ S = 9.7% avg +/-
 Circular Pipe 18" - 48 LF @ S = 4.2% avg +/-
 Trap/Vee Channel Flow - 144 @ S = 2.7% avg +/-

To - (DP 1)


Proposed Subcatchment - 14 (PSC-14)
 Proposed Conditions - Area = 153,054-SF (3.51AC)

Surface Conditions & Soils:
 36.5% 125A & 125B, Howard, Hydrologic Soil Group (HSG) A
 63.5% 107B, Conesus; 108B, Lansing; 53C & 53D, Valois-Howard, Hydrologic Soil Group (HSG) B

Runoff Curve Number = 61, >75% Grass, HSG B Soils
 Runoff Curve Number = 39, >75% Grass, HSG A Soils
 Runoff Curve Number = 98, Impervious, HSG A Soils
 Runoff Curve Number = 98, Impervious, HSG B Soils

Overland Stormwater Runoff - Longest Flowpath = 1,087lf +/-
 Sheet Flow, Short Grass - 86LF @ S = 9.3% avg +/-
 Trap/Vee Channel Flow - 177 LF @ S = 8.5% avg +/-
 Circular Pipe 24" - 32 LF @ S = 9.0% avg +/-
 Trap/Vee Channel Flow - 792LF @ S = 7.6% avg +/-


To - (DP 1)



REFERENCE HYDROCAD (HYDRAULIC & HYDROLOGIC) MODELING RESULTS PRESENTED WITH THESE PLANS
 PROPOSED ON-SITE CONDITIONS

REVISIONS
 No. Date SYM Description

HYDROLOGIC AND HYDRAULIC
 WORKSHEET - PROPOSED COND. 3
 STARR RD. RESIDENTIAL PUD
 STARR ROAD
 CORTLANDVILLE (T) N.Y.
 LEONIDAS GRP. OF VIRGIL, LLC
 5 SOUTH ST.-PO BOX 1107
 DRYDEN, N.Y. 13053






TIMOTHY C. BUHL, P.E.

35 FIRE LANE 24, AUBURN, N.Y. 13021 607 423-1919

DATE: 9-10-2018
 SCALE: N.T.S.
 DRAWN: MB/JLB
 JOB: 17-14
 SHEET:


ST-15



REVISIONS	
No.	Description


UTILITY SITE PLAN
 STARR RD. RESIDENTIAL PUD
 STARR ROAD
 CORTLANDVILLE (T) N.Y.

LEONIDAS GRP. OF VIRGIL, LLC
 5 SOUTH ST. PO BOX 1107
 DRYDEN, N.Y. 13053




TIMOTHY C. BUHL, P.E.
 35 FIRE LANE 24, AUBURN, N.Y. 13021 607.423.1919

DATE: 9-10-2018
 SCALE: 1" = 50'
 DRAWN: MB/JLB
 JOB: 1432
 SHEET: ST-16




NOTE: ROADWAY, WATER SUPPLY PIPING, & SEWER COLLECTION PIPING ARE ALL TO BE PRIVATELY OWNED, OPERATED, AND MAINTAINED.



REVISIONS	
No.	Description

SANITARY PROFILE


LEONIDAS GRP. OF VIRGIL, LLC
5 SOUTH ST., PO BOX 1107
DRYDEN, N.Y. 13053




TIMOTHY C. BUHL, P.E.

35 HIRELANE 24, AUBURN, N.Y. 13021 607 423-1919


DATE: 9-10-2018
SCALE: NOTED
DRAWN: JLB
JOB: 17-14
SHEET: ST-17



NOTE: ROADWAY, WATER SUPPLY PIPING, & SEWER COLLECTION PIPING ARE ALL TO BE PRIVATELY OWNED, OPERATED, AND MAINTAINED.




WATER PROFILE TO PARTI DRIVE



No.	Date	SYMBOL	Description

WATER PROFILE

LEONIDAS GRP. OF VIRGIL, LLC
 5 SOUTH ST., PO BOX 1107
 DRYDEN, N.Y. 13053



TIMOTHY C. BUHL, P.E.

35 FIRE LANE 24 AUBURN, N.Y. 13021 607.423.1919

DATE: 9-10-2018
 SCALE: NOTED
 DRAWN: JLB
 JOB: 17-14
 SHEET: ST-18


No.	Date	SY.M.	Description

SANITARY AND WATER DETAILS
 LEONIDAS GRP. OF VIRGLI, LLC
 5 SOUTH ST., PO BOX 1107
 DRYDEN, N.Y. 13053




TIMOTHY C. BUHL, P.E.
 35 FIRE LANE #4, AUBURN, N.Y. 13021 607 423-1919

DATE: 9-10-2018
 SCALE: NOTED
 DRAWN: JLB
 JOB: 17-14
 SHEET: ST-19




SANITARY SEWER LATERAL - GRAVITY

(SEE EFFLUENT SEWER DETAIL SHEETS FOR PVC FORCE MAINS)




TYPICAL TRENCH DETAIL

N.T.S.




TYP. CONN. TO EXIST. MANHOLE


N.T.S.



HYDRANT AND VALVE ASSEMBLY




PRE-CAST SANITARY MANHOLE




ENCASEMENT DETAIL

N.T.S.



SECTION @ 6" DI SPRINKLER RISER



HORIZONTAL

TEE	45°			22 1/2°			11 1/4°		
	L	D	L	L	D	L	L	D	
6"	2.5'	1.5'	2.0'	1.5'	1.5'	1.0'	1.5'	1.0'	
8"	3.5'	1.5'	2.5'	2.0'	1.5'	1.5'	2.0'	1.0'	
10"	3.5'	2.5'	3.0'	2.5'	3.0'	1.5'	2.5'	1.0'	
12"	4.0'	3.5'	4.0'	3.0'	3.5'	2.0'	3.0'	1.5'	


VERTICAL

TEE	45°			22 1/2°			11 1/4°		
	D	W	D	D	W	D	D	W	
6"	3.0'	5.0'	2.0'	4.0'	2.0'	3.0'	3.0'	3.0'	
8"	3.5'	5.0'	2.5'	4.0'	2.5'	3.0'	3.0'	3.0'	
10"	4.5'	5.0'	3.5'	4.0'	3.0'	3.0'	3.0'	3.0'	
12"	5.0'	5.0'	3.5'	4.0'	3.0'	3.0'	3.0'	3.0'	

- NOTES:
- INSTALL THRUST BLOCKS AT ALL TEES & ELBOWS
 - SIDES OF BLOCKS SHALL BE FORMED SO THAT NO CONCRETE CONTACTS BELLS, GLANDS, OR BOLTS
 - ALL CONC. FOR THRUST BLOCKS TO BE A MIN. OF 2500 P.S.I.


THRUST BLOCK DETAILS

N.T.S.




TYPICAL VALVE

N.T.S.







TYPICAL SEPARATION

N.T.S.



WATER SERVICE


NOTE: DUE TO SLOPE IN WATER LINE, INSTALL ABS TRENCH DAMS ALONG PIPE RUN.



REVISIONS	
No.	Description

SITE PHOTOMETRIC PLAN


STARR RD. RESIDENTIAL PUD LEONIDAS GRP. OF VIRGIL, LLC
STARR ROAD 5 SOUTH ST., PO BOX 1107
CORTLANDVILLE (D) N.Y. DRYDEN, N.Y. 13053



TIMOTHY C. BUHL, P.E.


35 HIRELANE 24, AUBURN, N.Y. 13021 607 423-1919

DATE: 9-10-2018
SCALE: 1" = 40'-0"
DRAWN: JLB
JOB: 17-14
SHEET: ST-20



LEGEND :

- SNOW STORAGE = SNOW
- PEDESTRIAN PATH =
- BUILDING LIGHT =
- STREET LIGHT =
- WATER VALVE =
- IMPROVED PICNIC PLAYGROUND AREA = P/P AREA



10" LETTER MONUMENT SIGN

SIGN NOTES


1. MONUMENT SIGN ON STARR ROAD TO BE TWO SIDED
2. 15.6 SF (LETTER/LOGO BOUNDARY) - FRAME SHOWN FOR MEASUREMENT PURPOSES ONLY.
3. BUILDING ANNOUNCEMENT SIGNS TO BE OF SIMILAR STYLE & MATERIALS BUT ONLY 4' - 8" X 8' IN SIZE, AND HAVE ONE ROW OF 8" LETTERS
4. ALL TRAFFIC CONTROL SIGNS WILL MEET MUTCD REQUIREMENTS, AND HC PARKING SIGNS AND PAVEMENT MARKINGS WILL MEET ADA REGULATIONS

REVISIONS	
No.	Description

SIGN LOCATIONS

LEONIDAS GRP. OF VIRGIL, LLC
 5 SOUTH ST. - PO BOX 1107
 DRYDEN, N.Y. 13053

STARR RD. RESIDENTIAL PUD
 STARR ROAD
 CORTLANDVILLE (T) N.Y.



TIMOTHY C. BUHL, P.E.

35 FIRE LANE 24, AUBURN, N.Y. 13021 607 423-1919

DATE: 9-10-2018
 SCALE: 1" = 50'
 DRAWN: MB/JLB
 JOB: 1432
 SHEET:
ST-21